

Fast and Accurate. Do it the...

KWIK-WAY®

102 Single-Pass Brake Lathe

*The
ORIGINAL
Single-Pass
Brake Lathe!*

**Efficiently machine Discs
and Drums for Cars and light
to medium duty Trucks.**

- Easy, single-cut operation guarantees OEM recommended (RMS) finish, regardless of depth
- Saves you time and increases your profits.
- FREE training video
- Own one for as little as two complete brake jobs per month!
- 5 year limited warranty—protects your investment.



Shown with optional
Heavy Duty Bench
(sold separately)

102 Single-Pass Brake Lathe

Ordering Information:

Model 102 Combo Brake Lathe – COMPLETE

With #1 Standard Adapter Kit included		102-0001-06
115V/60Hz/1Ph		102-0001-05
Optional Heavy Duty Bench (sold separately)		104-0200-00
Rotor Capacity **	6" - 20"	152mm - 508mm
Drum Capacity **	6" - 28"	152mm - 711mm
Drum Depth	7"	178mm
Flywheel Capacity †	6" - 20"	152mm - 508mm
Feed Rate (drum)	.005"	.127mm
Feed Rate (rotor)	.003"	.076mm
Spindle Speed	107 RPM	
Motor	1/2 Hp	
Electrical Requirement	115 volt (*220v option)	50/60 hz

** Requires optional arbor set (102-1069-00) for drums over 14" (356mm) and rotors over 16" (406mm)

† Flywheel adapter kit required (104-1039-00)

102 Single-Pass Brake Lathe – BASIC*

*Requires the purchase of ONE of the Adapter Kits listed below.

ADAPTER KIT #1

For vehicles up to 1/2 Ton		104-1000-01
Bell Clamps (2) 5-13/16" OD (148mm)		101-0235-40
Bell Clamp 4" OD (102mm)		109-1011-09
Bell Clamps 4-11/16" OD (119mm)		109-1012-06
Taper Cone #1 1-31/32" X 3-7/16" (50 X 87mm)		101-0236-05
Taper Cone #2 3-5/32" X 4-1/8" (80 X 105mm)		101-0237-02
Taper Cone #L 1-5/8" X 2-3/8" (41 X 60mm)		101-0243-00
Double Taper Cone #0 1.30" x 1.66" (33 x 42mm)		101-0260-02
Double Taper Cone #1 1.36" x 1.72" (35 x 44mm)		101-0260-12
Double Taper Cone #2 1.70" x 2.06" (43 x 52mm)		101-0260-22
Double Taper Cone #3 2.07" x 2.44" (53 x 62mm)		101-0260-32
Double Taper Cone #4 2.45" x 2.81" (62 x 71mm)		101-0260-42
Spacer 1" Long		109-1032-09
Spacer 2" Long (2)		109-1033-06
Silencing Belt, vented rotor		108-1061-00
Silencing Belt, drum		101-0230-10
1-1/2" Arbor Wrench		000-8700-21
Arbor Spring		000-1806-70
Wrench, Hex 3/32"		000-0600-46
T-Handle Wrench 5/32"		000-0600-66

ADAPTER KIT #2

For vehicles up to 3/4 Ton		104-1000-02
Double Taper Cone #0 1.30" x 1.66" (33 x 42mm)		101-0260-02
Double Taper Cone #1 1.36" x 1.72" (35 x 44mm)		101-0260-12
Double Taper Cone #2 1.70" x 2.06" (43 x 52mm)		101-0260-22
Double Taper Cone #3 2.07" x 2.44" (53 x 62mm)		101-0260-32
Double Taper Cone #4 2.45" x 2.81" (62 x 71mm)		101-0260-42
Double Taper Cone #5 2.84" x 3.19" (72 x 81mm)		101-0260-52
Double Taper Cone #6 3.19" x 3.56" (81 x 90mm)		101-0260-62
Master Hubless and Composite Rotor Adapter Set		102-0900-00
Spacer 1" Long		109-1032-09
Spacer 2" Long (2)		109-1033-06
Silencing Belt, vented rotor		108-1061-00
Silencing Belt, drum		101-0230-10
1-1/2" Arbor Wrench		000-8700-21
Wrench, Hex 3/32"		000-0600-46
T-Handle Wrench 5/32"		000-0600-66

ADAPTER KIT #3

For vehicles up to and including 1 Ton		104-1000-03
Double Taper Cone #0 1.30" x 1.66" (33 x 42mm)		101-0260-02
Double Taper Cone #1 1.36" x 1.72" (35 x 44mm)		101-0260-12
Double Taper Cone #2 1.70" x 2.06" (43 x 52mm)		101-0260-22
Double Taper Cone #3 2.07" x 2.44" (53 x 62mm)		101-0260-32
Double Taper Cone #4 2.45" x 2.81" (62 x 71mm)		101-0260-42
Double Taper Cone #5 2.84" x 3.19" (72 x 81mm)		101-0260-52
Double Taper Cone #6 3.19" x 3.56" (81 x 90mm)		101-0260-62
Master Kwik-Chuck Adapter		102-0800-50
Spacer 1" Long		109-1032-09
Spacer 2" Long (2)		109-1033-06
Silencing Belt, vented rotor		108-1061-00
Silencing Belt, drum		101-0230-10
1-1/2" Arbor Wrench		000-8700-21
Wrench, Hex 3/32"		000-0600-46
T-Handle Wrench 5/32"		000-0600-66

Call for a Distributor near you

1-800-553-5953

KW Products • 500 57th Street • Marion, IA 52302 USA
319-377-9421 • (FAX) 319-377-9101 • www.kwik-way.com